

Lampy LED - TUNELOWE

1/2



Model		SD48		SD96		SD144	
Moc oprawy [W]		60		120		180	
Strumień świetlny (lm)	Kąt świecenia	120°	140°	120°	140°	120°	140°
	5000-5800K	4170	4515	8935	8960	13000	13305
	4000-4500K	-	-	-	-	-	-
Ilość diod LED		48		96		144	
Źródło światła		Diody: Bridgelux, Cree - 1W każda					
CRI		Ra ≥ 65					
Soczewka		120° / 140°					
Napięcie wejściowe		100-240V AC					
Sprawność energetyczna		>82%		>85%			
Współczynnik mocy		≥ 0,90		≥ 0,95			
Zniekształcenia harmoniczne		<20%		<15%			
Temperatura pracy		-30° C do 50° C					
Żywotność		50 000h					
Standardy		CE (by TUV), RoHS, IP65					
Gwarancja		24 miesiące					
Wymiary [mm]		324x250x327		600x250x338,5		904x250x346	
Waga [kg]		8,6		15,0		22,1	

Lampy LED - TUNELOWE

2/2



Model		SE24		SE48		SE96		SE192	
Moc oprawy [W]		30		60		120		240	
Strumień świetlny (lm)	Kąt świecenia	-	-	120°	140°	120°	140°	120°	140°
	5000-5800K	-	-	4170	4515	8935	8960	13000	13305
	4000-4500K	-	-	-	-	-	-	-	-
Ilość diod LED		24		48		96		192	
Źródło światła		Diody: Bridgelux, Cree - 1W każda							
CRI		Ra ≥ 65							
Soczewka		120° / 140°							
Napięcie wejściowe		100-240V AC							
Sprawność energetyczna		>85%							
Współczynnik mocy		≥ 0,95							
Zniekształcenia harmoniczne		<15%							
Temperatura pracy		-30° C do 50° C							
Żywotność		50 000h							
Standardy		CE (by TUV), RoHS, IP65							
Gwarancja		24 miesiące							
Wymiary [mm]		765x200x334		765x245x334		765x347x334		765x527x334	
Waga [kg]		6,8		7,7		11,7		15,8	